



SMALLY XS D-MOTION

Domus Line
design

Recessed LED spotlight with diffuse light projection

Materials:

thermoplastic polymers, PMMA

Finishes:

chrome plated, aluminium, satin nickel,
steel, black touch, white matt

Light source:

twin LED module

Connector:

Micro24

Wiring:

2000mm

Application type:



universal

Installation:

recessed and on surface

Patented

SMALLY XS PLUS D-MOTION is a spotlight designed for recessed installation for $\varnothing 57$ mm hole with 12 mm depth integrating a twin LED cluster (2700 – 4000 K) with diffused light projection and no dot effect. **SMALLY XS PLUS D-MOTION** features the **innovative Plug&Play system (patented)**, for easy disconnection of the power cord from the spotlight. **SMALLY XS PLUS D-MOTION** is configured with two-pole cable, Micro24 connector, **TWA (Tunable White)** used for static or dynamic colour temperature selection with remote selector supplied separately.



| | |
|----------------------------|--------------------|
| Colour appearance | Tunable White |
| Colour temperature | 2700 - 4000 Kelvin |
| Luminous efficiency | 70 lm/W |
| CRI | Ra \geq 90 |



SMALLY XS PLUS TWA is a luminaire belonging to the new D-MOTION collection.




SMALLY XS PLUS TWA   


| Code | Watt & Volt |
|------|-------------|
| | 3W @ 24Vdc |

CONVERTER AND TWA SELECTOR NOT INCLUDED.
TO BE ORDERED SEPARATELY.



| Code | Finish |
|------|---------------|
| 09 | chrome plated |
| 10 | aluminium |
| 17 | satin nickel |
| 19 | steel |
| 46 | black touch |
| 54 | white matt |

 This drawing shows the spotlight's overall dimensions. See installation manual for more details.



ON REQUEST ARE AVAILABLE SETS WITH 2, 3, 4, 5 **SMALLY XS PLUS TWA**, POWER SUPPLY AND COLOUR SELECTOR.



Tunable White (TWA) luminaires of the D-MOTION collection allow the static or dynamic colour temperature selection (2700 - 4000 K) by a remote selector supplied separately.



SMALLY XS PLUS D-MOTION features the innovative **Plug&Play system (patented)**, for easy disconnection of the power cord from the spotlight.



Spacers are available on request for surface installation:

| Code | Finish |
|----------|--------------------|
| 20125_ _ | see finishes codes |



Inclined spacers are available on request for surface installation:

| Code | Finish |
|----------|--------------------|
| 20124_ _ | see finishes codes |

FINISHES



CHROME PLATED (code 09)



ALUMINIUM (code 10)



SATIN NICKEL (code 17)



STEEL (code 19)



BLACK TOUCH (code 46)



WHITE MATT (code 54)

For LED converters and accessories consult the **Domus Extra catalogue** also available on www.domusline.com.

